











Model	Trs2
Use	Technical
Lenght	780mm(30.71")
Ø Body	210mm(8.27")
Ø Conveyor	335mm(13.19")
Material	Marin AllAbs
Total Weight	21.5kg(47.40lb)
Closure	Central screw

Battery Type	Li-ion
Voltage	25.2V
Power	29.8Ah
Nominal Capacity	750Wh
Dry Battery	Yes
Cut Off + Alarms	Yes
Residual Battery	External Viewer

Max Trust	270N(60.7lbf)
Max Speed	70m/'(229ft/')
Range Max/Cr/Min	80'/160'/240'
Max Deep	200m(656.17ft)
Water Temperature	-5/+35°C (23/95°F)
Software	"Pilota 5"
Way of Use	Linear/Sequential
N° Speed	5
Acceleration Ramp	Programmable
Motor	Permanent Magnets

€ 4000+Vat Price

Battery Charger 90-240V 50-60Hz **Charging Time** 5h

Options















Conveyor + Propeller Carbon







Saddle Travel Carrying





Transport Case



Torsion Attenuator



Central locking



Battery Status Monitor on Canister

Note:
Duration varies depending on the speed, the position and the equipment of diver, and is misured in continuos ignition.
Duration is specified at max. speed 100% - cruise speed 50% - min speed 30%
Maximum speed is with the aid of standard propeller with 3 blades and the load of an average diver with double tanks 12+12.
Way of use is choose with the aid of software "Pilota 5" and may be Linear or Sequential.
Neutral trim in fresh and salt water obtained by placing two different weights.
Price is VAT and shipped excluded. Price is valid for EU Countries. Price out EU call direct dealer or our sales service.